



**RESPAIR P3V  
ECONOMY  
DISPOSABLE  
RESPIRATOR**

**MOULDED DISPOSABLE DUST MASK**

**CONFORMITY**

Meets the FFP3 requirements of EN149:2001+A1:2009.  
EC Certificate Number 505403, issued by BSi Product Certification.  
Product Certification, in accordance with the PPE Directive 89/686/EEC.

**PERFORMANCE**

Offers an assigned protection factor (APF) of 20 x Occupational Exposure Standard (OES) for fine toxic dusts, fibres, fumes and mists.

**MARKINGS**

EN149: 2001+A1:2009 FFP3 (NR)

**MATERIALS**

Man made fibres. Polypropylene co-polymer exhalation valve with rubber diaphragm.

**INSTRUCTIONS FOR USE**

Mask must be fitted in accordance with the instructions supplied. Care must be taken to ensure that the correct mask type is selected for the work to be carried out. If in doubt as to the type of mask required seek professional advice.

**LIMITATIONS OF USE**

Protection will only be offered if the mask is fitted correctly. The mask must be discarded and replaced if it is a). Removed whilst in the contaminated area, b). Breathing difficulties due to clogging are experienced or, c). The mask becomes damaged.



The mask, when in contact with the skin may cause allergic reactions to susceptible individuals. If this occurs leave the hazard area, remove mask and seek medical advice.

**NOTES**

- Use in well ventilated areas only, which are not deficient in oxygen and do not contain explosive atmospheres.
- This mask is not designed to be worn by people with facial hair.

**CLEANING & MAINTENANCE**

Not applicable – disposable product. Store the masks out of direct sunlight away from chemicals and in a dry atmosphere.



## FITTING INSTRUCTIONS

1. Hold the mask firmly and place the bottom headband over the head to the nape of the neck.
2. Place the mask under the chin, then over the nose, putting the top headband over the crown of the head.
3. Ensure a good fit by pulling the elastic through the clips and adjust for comfort.
4. Ensure that the nose clip is moulded around the nose securely.

## FIT CHECK

Check the fit of the mask by covering with both hands and exhale vigorously. Any leaks around the face seal must be eliminated before entering contaminated area.

## INSTRUCTIONS FOR USE

1. Suitable for use against solid and liquid particulates including oil based mists.
2. This product does not protect against gases or where oxygen levels are below 17%.
3. Do not use when concentrations or contaminants are unknown or dangerous to life.
4. Leave the work area if distress or dizziness occurs.
5. Do not alter or modify the product in any way.
6. This product is intended only for single use and must not be used for more than 8 hours. Replace mask if contaminated or if breathing becomes difficult.
7. Facial hair may affect the efficiency of the product.
8. Do not use in an explosive area.
9. Ensure the product is suitable for the intended use.
10. Place/protect the product when not in use within its packaging.
11. Store within +5° C - +32° C. Store at <80% RH.

## FACE FIT TEST KITS & TESTING SERVICES



### Why carry out face fit testing?

Over the years, awareness to Occupational Health has greatly improved. Misuse of Respiratory Protective Equipment (RPE) has been fairly commonplace. From facial hair interfering with the seal on the face to tearing off the bottom strap of the respirator, to

burning holes in the filter, allowing the wearer to smoke through it, has been common practice.

Legislation, through the COSHH Approved Code of Practice (ACoP) has been put in place in an attempt to eliminate this abuse and improve awareness even further. This Face Fit Test Kit has been developed using the structure as laid down in HSE 282/28 Document. The Health and Safety Executive (HSE) suggest that Qualitative Face

Fit Testing should be conducted on all 'tight fitting' filtering face pieces and half mask respirators.

### How we can help

A qualified member of our team can visit your premises to carry out the face fit test to ensure the complete safety of your staff. We are able to test as many pieces of equipment as you like during our visit using our face fit testing kit.

### How it works

The nebuliser produces a mist measuring approximately 5 microns. If the wearer tastes the substance, the seal has been broken and the wearer must be re-tested. This is a perfectly safe process which could save someone's life.

**Contact us to discuss Face Fit Testing.**